



## ADVANTAGES

- Two burners
- 
- Set of hyper-realistic logs
- 
- Multi-program remote control
- 
- Invisible safety screen
- 
- Efficient heating
- 
- Minimalist design
- 
- Easy to use
- 
- Energy saving



Size	B-60	B-80	B-100	B-100 H
Efficiency Energuide (NG   LPG)	68.2%   65.2%	68.2%   65.2%	66.2%   67.2%	65.2%   66%
Maximum power (BTU)	1 burner 28 200 2 burners 47 000	1 burner 28 200 2 burners 47 000	1 burner 28 200 2 burners 47 000	1 burner 30 000 2 burners 50 000
Minimum power. (BTU)	1 burner 16 450 2 burners 28 200	1 burner 16 450 2 burners 28 200	1 burner 16 450 2 burners 28 200	1 burner 17 500 2 burners 30 000
Heating surface area	1 350 ft <sup>2</sup>	1 350 ft <sup>2</sup>	1 350 ft <sup>2</sup>	1 450 ft <sup>2</sup>
Weight	318 lb	315 lb	284 lb	435 lb
Direct vent	4/7	4/7	5/8	5/8
Valve and regulator	Maxitrol	Maxitrol	Maxitrol	Maxitrol
Convection system	standard	standard	standard	standard
A - Width*	42 <sup>7</sup> / <sub>16</sub> "	50 <sup>5</sup> / <sub>16</sub> "	58 <sup>1</sup> / <sub>16</sub> "	58 <sup>1</sup> / <sub>16</sub> "
B - Height	44"	39 <sup>3</sup> / <sub>4</sub> "	27 <sup>1</sup> / <sub>8</sub> "	44 <sup>7</sup> / <sub>16</sub> "
C - Depth*	21"	21"	20 <sup>5</sup> / <sub>16</sub> "	21"
D - Opening width	23 <sup>5</sup> / <sub>8</sub> "	31 <sup>1</sup> / <sub>2</sub> "	39 <sup>1</sup> / <sub>4</sub> "	39 <sup>1</sup> / <sub>4</sub> "
E - Opening height	31 <sup>1</sup> / <sub>2</sub> "	25 <sup>7</sup> / <sub>8</sub> "	13 <sup>9</sup> / <sub>16</sub> "	25 <sup>7</sup> / <sub>8</sub> "
F - Chimney position*	10 <sup>5</sup> / <sub>8</sub> "	10 <sup>5</sup> / <sub>8</sub> "	9 <sup>15</sup> / <sub>16</sub> "	10 <sup>5</sup> / <sub>8</sub> "

\* Dimensions including stand-off