



ADVANTAGES

- Two burners
-
- Set of hyper-realistic logs
-
- Multi-program remote control
-
- Invisible safety screen
-
- Efficient heating
-
- Minimalist design
-
- Easy to use
-
- Energy saving



Size	B-95 CL	B-95 CR
Efficiency Energuide (NG LPG)	65.2% 68.3%	65.2% 68.3%
Maximum power (BTU)	1 burner 28 200 2 burners 47 000	1 burner 28 200 2 burners 47 000
Minimum power. (BTU)	1 burner 16 450 2 burners 28 200	1 burner 16 450 2 burners 28 200
Heating surface area	1 350 ft ²	1 350 ft ²
Weight	230 lb	230 lb
Direct vent	5/8	5/8
Valve and regulator	Maxitrol	Maxitrol
Convection system	standard	standard
A - Width*	49 ⁹ / ₁₆ "	49 ⁹ / ₁₆ "
B - Height	24 ¹³ / ₁₆ "	24 ¹³ / ₁₆ "
C - Depth*	23 ¹³ / ₁₆ "	23 ¹³ / ₁₆ "
D - Opening width	38 ¹⁵ / ₁₆ "	38 ¹⁵ / ₁₆ "
E - Opening height	15 ¹ / ₈ "	15 ¹ / ₈ "
F - Opening depth	16 ⁵ / ₁₆ "	16 ⁵ / ₁₆ "
G - Chimney position*	11 ³ / ₈ "	11 ³ / ₈ "

* Dimensions including stand-off