



### ADVANTAGES

- Heating power adapted to the smallest spaces
- Precision assembly
- Automatic combustion air inlet calibration
- Produces little ash
- Easy to light
- Fits all masonry hearths
- Energy-efficient performance



● **66x50**



● **76x60**







Size	● <b>66x50</b>	● <b>76x60</b>
Certification	EPA 2020   CSA B415 ULC S628   UL 1482-7	EPA 2020   CSA B415 ULC S628   UL 1482-7
Efficiency (EPA)	68,4%	68,3%
Maximum length of logs	16"	20"
Maximum power (BTU)	34 000	48 000
Heating surface area	1 000 pi <sup>2</sup>	1 400 pi <sup>2</sup>
Firebox size	1.08 pi <sup>3</sup>	1.58 pi <sup>3</sup>
Particle emissions	1,93 g/h	1,89 g/h
Weight	165 lb	200 lb
Outside air duct	ø 4"	ø 4"
Floor protection	36 9/16" x 16 1/8"	40 1/2" x 16 1/8"
Glass width	20 9/16"	24 1/2"
Glass height	12 1/16"	16"

\* This model will be launch in fall 2021.  
Dimensions for information only. See the installation manuals for details.

# FINISHING FRAMES

## REQUIRED ACCESSORY

Choose from the following options:

				*Available soon	
					
		<b>66X50</b>		<b>76X60</b>	
THIN EDGE		Width	26"	29 <sup>15</sup> / <sub>16</sub> "	
		Height	19 <sup>11</sup> / <sub>16</sub> "	23 <sup>5</sup> / <sub>8</sub> "	
PICTURE TYPE 2"		Width	29 <sup>3</sup> / <sub>8</sub> "	33 <sup>5</sup> / <sub>16</sub> "	
		Height	21 <sup>3</sup> / <sub>8</sub> "	25 <sup>5</sup> / <sub>16</sub> "	
PICTURE TYPE 4"		Width	33 <sup>5</sup> / <sub>16</sub> "	37 <sup>1</sup> / <sub>4</sub> "	
		Height	23 <sup>3</sup> / <sub>8</sub> "	27 <sup>5</sup> / <sub>16</sub> "	
PICTURE TYPE 6"		Width	37 <sup>1</sup> / <sub>4</sub> "	41 <sup>3</sup> / <sub>16</sub> "	
		Height	25 <sup>5</sup> / <sub>16</sub> "	29 <sup>1</sup> / <sub>4</sub> "	

\* This model will be launch in fall 2021.  
 Dimensions for information only. See the installation manuals for details.

## AVAILABLE COLOR



Matte black – STOVE BRIGHT 6304